

Package: WAreg (via r-universe)

May 12, 2026

Type Package

Title While-Alive Regression for Composite Endpoints with CRT-Robust Inference

Version 0.1.0

Description Implements while-alive regression for composite endpoints with recurrent and terminal events. Supports flexible time bases (B-spline, natural spline, M-spline, piecewise polynomial, interval-local, etc.), cluster-robust inference for cluster randomized trials, prediction, plotting, and K-fold cross-validation.

License GPL-3

Encoding UTF-8

Depends R (>= 4.1)

Imports dplyr, tidyr, tibble, ggplot2, survival, nleqslv, splines, MASS, magrittr

Suggests splines2, testthat (>= 3.0.0), knitr, rmarkdown

Config/testthat/edition 3

URL <https://example.com/WAreg>

BugReports <https://example.com/WAreg/issues>

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

LazyData true

Config/pak/sysreqs libicu-dev

Repository <https://fancy575.r-universe.dev>

Date/Publication 2025-11-09 21:53:53 UTC

RemoteUrl <https://github.com/fancy575/wareg>

RemoteRef HEAD

RemoteSha 0e811e910defa643a788b9473b2b5bc5288cb249

Contents

crt_dt	2
irt_dt	3
plot.WA	4
predict.WA	5
summary.WA	6
WA_cv	7
WA_fit	8

Index	11
--------------	-----------

crt_dt	<i>Clustered Recurrent-Time Dataset: crt_dt</i>
--------	---

Description

A simulated dataset of clustered recurrent events with terminal/censoring outcomes and covariates, suitable for examples and tests.

Usage

```
data(crt_dt)
```

Format

A data frame with the following columns:

id Integer subject ID (within the whole sample).

cluster Integer cluster ID.

time Numeric event/censoring time.

status Integer event type indicator: 0 = censored, 1 = recurrent type 1, 2 = recurrent type 2, 3 = death (terminal).

trt Cluster-level treatment indicator carried to subjects (e.g., 0/1).

Z1 Numeric covariate.

Z2 Numeric covariate.

Details

Rows represent observed events (including censoring and death) for each subject. Multiple rows per id indicate multiple recurrent events; terminal/censoring rows mark the end of observation for that subject.

Source

Generated by the package's simulation utilities.

plot.WA

Plot while-alive trajectory or a covariate's time-varying effect

Description

Plot while-alive trajectory or a covariate's time-varying effect

Usage

```
## S3 method for class 'WA'
plot(
  x,
  newdata,
  t_seq,
  id = 1,
  mode = c("wa", "cov"),
  covariate = NULL,
  ylab_wa = "While-alive loss rate",
  ylab_cov = NULL,
  xlab = "Time",
  level = 0.95,
  smooth = FALSE,
  span = 0.3,
  ...
)
```

Arguments

x	A "WA" object.
newdata	Data used to rebuild the RHS design (same columns as in the model).
t_seq	Times to plot over (numeric vector).
id	Row index of newdata to use for the while-alive trajectory (mode = "wa").
mode	"wa" to plot the while-alive loss rate, or "cov" to plot a specific covariate's time-varying effect.
covariate	Character; covariate name (must appear on RHS) when mode="cov".
ylab_wa	Y-axis label for while-alive plot.
ylab_cov	Y-axis label for covariate-effect plot; default "Effect of <covariate> on $\lambda(t)$ ".
xlab	X-axis label.
level	Confidence level for ribbons (default 0.95).
smooth	Logical; if TRUE, apply LOESS smoothing to the displayed curve/CI.
span	LOESS span used when smooth=TRUE.
...	Unused.

Value

A **ggplot2** object.

Examples

```
## Not run:
plot.WA(fit, newdata = crt_dt,
        t_seq = seq(0, max(fit$tau_grid), length.out = 200),
        id = 1, mode = "wa", smooth = TRUE)

plot.WA(fit, newdata = crt_dt,
        t_seq = seq(0, max(fit$tau_grid), length.out = 200),
        id = 1, mode = "cov", covariate = "numchron",
        ylab_cov = "Effect of numchron on linear predictor",
        smooth = TRUE)

## End(Not run)
```

predict.WA	<i>Predict while-alive loss rates</i>
------------	---------------------------------------

Description

Predict while-alive loss rates

Usage

```
## S3 method for class 'WA'
predict(object, newdata, t_seq, level = 0.95, ...)
```

Arguments

object	A "WA" object.
newdata	Data frame with columns matching the RHS of the fitted model. Predictions are computed for the rows of newdata.
t_seq	Numeric vector of times at which to evaluate predictions.
level	Confidence level for pointwise intervals (default 0.95).
...	Unused.

Value

A data frame with columns `id` (row index in `newdata`), `t`, `mu` (predicted while-alive rate), and CI columns `lb`, `ub`.

Examples

```
## Not run:
newdata_ex <- crt_dt |>
  dplyr::select(intv, demo_sex_male, numchron) |>
  dplyr::distinct() |>
  dplyr::slice(1:2)
pred <- predict.WA(fit, newdata = newdata_ex, t_seq = seq(0, 3.5, by = 0.05))
head(pred)

## End(Not run)
```

summary.WA

*Summarize a WA object***Description**

Summarize a WA object

Usage

```
## S3 method for class 'WA'
summary(object, ...)
```

Arguments

object	A "WA" object from WA_fit .
...	Unused.

Value

An object of class "summary.WA" containing configuration and a coefficient table with estimates, standard errors, and z-scores.

Examples

```
## Not run:
fit <- WA_fit(Surv(time, status) ~ intv + demo_sex_male + numchron,
  crt_dt, id="screenid", cluster="practiceid",
  knots=seq(0,3.5,length.out=6), tau_grid=seq(0,3.5,length.out=6),
  basis="bz", degree=1, link="log",
  w_recur=c(1), w_term=2, ipcw="cox",
  ipcw_formula=~ demo_sex_male + numchron)
summary(fit)

## End(Not run)
```

Description

Runs K-fold CV over a grid of basis types, degrees, interior-knot counts, and link functions. For each configuration, fits the model on K-1 folds and accumulates the prediction error (PE) on the held-out fold using `WA_PE()` (IPCW computed on the training subjects).

Usage

```
WA_cv(
  formula,
  data,
  id,
  cluster = NULL,
  basis_set = c("il", "pl", "bz"),
  degree_vec = 1:2,
  n_int_vec = c(0, 2, 4),
  knot_scheme = c("equidist", "quantile"),
  link_set = c("log"),
  time_range = NULL,
  tau_grid = NULL,
  w_recur,
  w_term,
  ipcw = c("cox", "km"),
  ipcw_formula = ~1,
  K = 5,
  seed = 1L,
  verbose = TRUE
)
```

Arguments

<code>formula</code>	<code>data</code> , <code>id</code> , <code>cluster</code> See WA_fit .
<code>basis_set</code>	Character vector of candidate bases.
<code>degree_vec</code>	Integer vector of candidate degrees.
<code>n_int_vec</code>	Integer vector of interior-knot counts; 0 means boundaries only.
<code>knot_scheme</code>	"equidist" or "quantile" to construct interior knots.
<code>link_set</code>	Character vector of candidate links (subset of <code>c("log", "identity")</code>).
<code>time_range</code>	Optional numeric length-2 vector <code>c(tmin, tmax)</code> . If NULL, inferred from data.
<code>tau_grid</code>	Optional numeric vector; if NULL, a default dense grid over <code>time_range</code> is created.
<code>w_recur</code>	<code>w_term</code> Event-type weights (see WA_fit).

ipcw	IPCW method ("cox" or "km") for PE computation.
ipcw_formula	One-sided RHS formula for IPCW Cox model (if ipcw="cox").
K	Number of folds.
seed	RNG seed for fold assignment.
verbose	Logical; show a text progress bar and per-fold messages.

Value

A data frame with columns: basis, degree, n_int, link, and aggregated PE. Lower PE is better.

Examples

```
## Not run:
tmin <- 0
tmax <- max(crt_dt$time, na.rm = TRUE)
cv_tab <- WA_cv(
  Surv(time, status) ~ intv + demo_sex_male + numchron,
  data = crt_dt, id = "screenid", cluster = "practiceid",
  basis_set = "bz", degree_vec = c(1,2,3,4),
  n_int_vec = c(0,2,3,4,5),
  knot_scheme = "equidist",
  link_set = "log",
  time_range = c(tmin, tmax),
  tau_grid = seq(0, 3.5, length.out = 6),
  w_recur = c(1), w_term = 2,
  ipcw = "cox", ipcw_formula = ~ demo_sex_male + numchron,
  K = 5, seed = 2025
)
head(cv_tab[order(cv_tab$PE), ], 10)

## End(Not run)
```

WA_fit

While-Alive Regression (WA) for Composite Endpoints

Description

Fits the while-alive regression model targeting the while-alive loss rate for composite endpoints with recurrent and terminal events. Time-varying covariate effects are represented via user-chosen time bases (e.g., B-spline, piecewise polynomial, interval-local). Robust inference supports cluster-randomized trials (CRTs) via cluster-robust variance; if `cluster = NULL`, IID (subject-as-cluster) variance is used.

Usage

```

WA_fit(
  formula,
  data,
  id,
  cluster = NULL,
  knots,
  tau_grid,
  basis = c("il", "pl", "bz", "ns", "ms", "st", "tl", "tf"),
  degree = 1,
  link = c("log", "identity"),
  w_recur,
  w_term,
  ipcw = c("km", "cox"),
  ipcw_formula = ~1
)

```

Arguments

formula	A <code>Surv(time, status) ~ RHS</code> formula. <code>time</code> and <code>status</code> must exist in <code>data</code> . The RHS contains baseline covariates (no explicit time-varying covariates here; time-variation is induced via the chosen basis).
data	Long-format data frame with one row per <i>event/checkpoint</i> per subject, containing <code>time</code> , <code>status</code> , <code>id</code> , optional <code>cluster</code> , and RHS covariates.
id	Character scalar; subject ID column name.
cluster	Optional character scalar; cluster column name for CRT-robust inference. If <code>NULL</code> , IID inference treats each subject as its own cluster.
knots	Numeric vector (length ≥ 2) specifying the basis boundaries and optional interior knots that define the time basis shape.
tau_grid	Numeric vector of evaluation times used to stack the estimating equations. Independent of knots.
basis	One of <code>"il"</code> , <code>"pl"</code> , <code>"bz"</code> , <code>"ns"</code> , <code>"ms"</code> , <code>"st"</code> , <code>"tl"</code> , <code>"tf"</code> : interval-local (<code>"il"</code>), piecewise polynomial (<code>"pl"</code>), B-spline (<code>"bz"</code>), natural spline (<code>"ns"</code>), M-spline (<code>"ms"</code> , requires splines2), step (<code>"st"</code>), truncated linear (<code>"tl"</code>), or time-fixed (<code>"tf"</code>).
degree	Integer degree for bases that use it (e.g., <code>"bz"</code> , <code>"pl"</code> , <code>"ns"</code> , <code>"ms"</code>).
link	Link function: <code>"log"</code> (default) or <code>"identity"</code> .
w_recur	Numeric vector of weights for each recurrent event type. Its length must match the number of recurrent status codes in <code>data</code> (i.e., excluding \emptyset for censoring and the max code for terminal).
w_term	Numeric scalar; weight for the terminal event.
ipcw	IPCW method: <code>"km"</code> or <code>"cox"</code> .
ipcw_formula	A one-sided formula specifying RHS covariates for the IPCW Cox model when <code>ipcw = "cox"</code> (e.g., <code>~ x1 + x2</code>). Ignored for <code>ipcw = "km"</code> .

Details

The estimating equations solve $E[Z(t)\{L(t) - \mu_{\beta}(t)X_{\min}(t)\}V/G] = 0$ over `tau_grid`, where $L(t)$ is the weighted composite loss (recurrent+terminal), $\mu_{\beta}(t)$ the while-alive loss rate under the chosen link, $X_{\min}(t) = \min(T, t)$, V the at-risk/terminal indicator, and G the censoring survival modeled via ipcw.

Value

An object of class "WA" with elements:

- `est`: named coefficient vector.
- `vcov`: cluster-robust variance matrix.
- `se`: standard errors.
- `converged`: logical.
- `basis`, `degree`, `link`, `Z_cols`, `knots`, `tau_grid`, `id_var`, `cluster_var`, `w_recur`, `w_term`, `status_codes`, `formula`.

Examples

```
## Not run:
# Example (non-running) using included 'crt_dt' long dataset
fit <- WA_fit(
  Surv(time, status) ~ intv + demo_sex_male + numchron,
  data      = crt_dt,
  id        = "screenid",
  cluster   = "practiceid",
  knots     = seq(0, 3.5, length.out = 6),
  tau_grid  = seq(0, 3.5, length.out = 6),
  basis     = "bz", degree = 1, link = "log",
  w_recur   = c(1), w_term = 2,
  ipcw      = "cox", ipcw_formula = ~ demo_sex_male + numchron
)
s <- summary(fit)

## End(Not run)
```

Index

* datasets

crt_dt, 2

irt_dt, 3

crt_dt, 2

irt_dt, 3

plot.WA, 4

predict.WA, 5

summary.WA, 6

WA_cv, 7

WA_fit, 6, 7, 8